

UROVO

K388S Mobile Labeling Printer

- High-speed scan printing with built-in peeling, instant scanning, and pasting for efficient handling of incoming goods, returns, exchanges, and damaged labels, ensuring improved labeling speed and accuracy.
- Support 1D/2D codes scanning and printing, effortlessly replacing damaged or creased labels with greater speed and accuracy.
- Equipped with an Octa-core 2.45GHz Android terminal and a 5.7-inch large screen display for seamless and convenient operation.
- Adaptable to labels with widths ranging from 30mm to 80mm, meets the demands of printing labels of different sizes in various scenarios.
- The removable 32.4Wh battery delivers long-lasting working hours and easy charging with a Type-C port.
- Support both forward and reverse supply roll, easy installation and swift paper replacement.



1D/2D Barcodes
Scanning



Print Speed - Up to
126 mm/sec



Resolution:
203dpi(8 pm / mm)



Automatic Label
Peeling



5.7 in Display

• Printing features

Print method: Thermal direct
Print width: 30mm-80mm
Supply roll diameter: ≤82mm
Supply roll thickness: 50 ~ 180μm
Printer life: 100km (12.5% black printing or below) per point: 100 million pulses (25°C)
Command set: CPCL, ZPL, EPL, TSPL, ESC-POS (optional)
Label positioning: Penetrative
Cover opening: One-touch opening
Paper removal detection: Proximity sensor (optional)
Error detection: Paper out, low battery, open cover, peeled paper not removed(optional proximity sensor)

• Environmental

Working temperature: 5°C~+40°C
Storage temperature: -20°C~+50°C
Operating humidity (relative humidity): 5%~90%

• Android Terminal

CPU: Octa-core 2.45GHz
O.S.: Android 11.0
Memory: 4GB+64GB
Display: 5.7 in display , 720*1440
Scanning: Professional Scanning Heads, support international standard 1D/2D barcodes
Bluetooth: BT 5.0+BR/EDR+BLE
Wi-Fi: 2.4G/5G
IEEE: 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax ready

• Dimensions

198mm*105mm*170mm
Weight: (without battery and supply rolls): 772g/
with Battery: 946g

• Power Supply

Battery: 32.4Wh (3000mAh) /10.8V rechargeable lithium-ion battery
Charging: Charged directly or through the battery
Inches per charge: Up to 200 meters(12.5% black printing)
Adapter: 5V2A